



Video Conferencing Camera



Record your meeting in full HD



Best device for virtual conference



Easy to setup and mounting option



Comes with optical and digital zoom

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com

Video Conferencing Camera	UE-CAM-20
Digital Zoom	10x
Optical Zoom	20x
Camera Resolution	1080p 60fps, 1080p 30fps
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Sensor	1/2.7" CMOS Sensor
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Digital Noise Reduction	2D&3D Digital Noise Reduction
Effective Pixels	2.07M
Scanning Mode	Progressive
Lens Focus Arrangement	f4.42mm ~ 88.5mm, F1.8 ~ F2.8
Video S/N	≥55dB
Horizontal/Vertical Angle of View	60.7 degrees / 34.1 degrees
Horizontal/Vertical Rotation Range	±170 degree - Minus 30 degrees ~ Plus 90 degree
Pan Speed Range	1.7 degrees ~ 100 degrees
Tilt Speed Range	1.7 degrees ~ 70 degrees
Image Freeze	Support
Video Resolution	1080p/60, 1080p/50, 1080i/60, 1080i/50, 1080p/30, 1080p/25, 720p/60, 720p/50
Number of Presets and accuracy	255, 0.1°
Audio Encoding	AAC audio encoding for better sound quality and smaller bandwidth
Local Storage	Local storage module directly recording to local USB flash disk
Low Light	High SNR of CMOS sensor even under low illumination conditions picture can still keep clean and clear
Remote Control	All parameters of the camera remotely controlled by the high-speed communications, handheld remote control
Video Output	HDMI x 1, USB 3.0 x 1
SD Output	CVBS: 3.5mm x1
Network Interface	RJ45: 10M/100M Ethernet Interface
Audio Interface	1-ch: 3.5mm Audio Interface, Line In
Communication Interface	RS232 In x 1, RS232 Out x 1, RS485 x 1
Video Bit Rate and Type	32Kbps ~ 2048Kbps, Variable Rate, Fixed Rate
Frame Rate	50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps
Audio Bit Rate	AAC, 96Kbps, 128Kbps, 256Kbps
Support protocols	TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.
USB and Power Jack	USB 2.0 x 1, USB 3.0 x1
Video Stream	H.265/H.264/MJPEG, Main Stream, Sub Stream
Main Stream Resolution	1920x1080,1280x720,1024x576
Sub Stream Resolution	720x576, 720x480, 320x240
Input Voltage	DC 12V
Current Consumption	1.0A (Max)
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)

Product images are for illustrative purposes only and may differ from the actual product.



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
 Ph.: 05946-255434, Fax: 05946-252300
 Email: universalenterprises111@gmail.com

Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption	12W (Max)
Accessories	IR remote control, cables, Power adaptor and cable, user manual

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com