



Amplifier



4 Mic Inputs

Overheat protection

overcurrent protection

Cooling Fan

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com

Amplifier- UE-1500A	
Amplifier	Class D
Rated Power	150 W
Impedence	MIC input: 5mV / 600Ω balanced; AUX1,2 input: 350mV / 10KΩ unbalanced RCA connection terminal
Mic Input	4 input
Line Input	2 input
Output	MIX OUT: 1000mV / 470Ω unbalanced RCA connector
Tone	Bass: ± 10dB at 100Hz; Treble: ± 10dB at 10KHz
Frequency Response	80Hz ~16KHz (+ 1dB, -3dB)
SNR	MIC1,2,3: 66dB; AUX1,2: 85dB
THD	< 0.05% (at 1KHz, 1/3 rated power)
Mute Function	MIC 1 is prior to MIC2-4, AUX1-2 audio input; EMC is prior to all audio inputs
Heat Dissipation	Side-in and rear-out forced fan cooling; fan starts automatically when the device is turned on; infinitely variable speed
Channel Crosstalk Attenuation	≥50dB
Protection	Overheat protection, overcurrent protection, short circuit protection
Power Supply	AC ~ 220V / 50Hz
Power Consumption	180W

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
 Ph.: 05946-255434, Fax: 05946-252300
 Email: universalenterprises111@gmail.com