



Video Wall



Low Maintenance & Power Saving



Uniform Brightness and Colours



Bezel-Less Viewing Experience



Wide Viewing Angles

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mongal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com

Video Wall	UE-IP-9A
Environment	Indoor
Maintenance	Front
Installation mechanism	Easy Maintenance, self-locking mechanism for easy & fast installation, Automatic Alignment Mechanism
Drive Mode	Constant Current Drive
Brightness	600 cd/m ²
Pixel Pitch	1.9 mm
LED Type	3-in-1 black SMD
Pixel Configuration	1 Red, 1 Green, 1 Blue
Brightness Control	Manual/Automatic
Contrast Ratio	5000:1
Colour Temperature	3200-9000 K
Material	Highly Modular and Indigenized Indian Design as per Indian Environment
Brightness Uniformity	≥97 %
Viewing Angle	H: 160 degrees; V:140 degree
Viewing Distance	≥1.9 m
Flatness of Unit Case	± 0.3mm
Operating Temperature	-10 degree C ~ +40 degree C
Operating Humidity	10~80%RH
Pixel Density	262144 pixels / m ²
Processing Depth/ Grey Scale	14~16 bit
High Dynamic Range	Supported
Acoustic Noise	Fanless operation
LED Wall Size	6000 x 1650mm
Gap Between Modules	Seamless Zero Beze
Frame Rate	50Hz
Refresh Rate	≥ 3840 Hz
Input Voltage	100-240V AC
Input Power Frequency	50/60Hz
Power Consumption	600 (W/m ²)
LED Lifetime	≥100,000 Hours
LED Wall Controller	
Input	1x Audio, 1x DVI
Output	1x LED Outputs over Ethernet
Control	1x USB, 1x URT in, 1x URT out
Accessory	1x 4 pin Light Sensor Interface
Overall power consumption	16W
Working Temperature	-10 Degree C ~+50 degree C
Working Humidity	0%~95%
Video wall Controller and accessories	Video controller, Multi viewer (upto 4 in and out), HDMI Splitters and Switchers for input out controls, Drive, signal amplification
Input Voltage	AC-100-240V-50/60HZ