

## **Video Conferencing Camera**



- Record your meeting in full HD
  - Best device for virtual conference
- Easy to setup and mounting option
  - Comes with optical and digital zoom

Product image(s) are for illustrative purposes only and may differ from the actual product



## UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand) Ph.: 05946-255434, Fax: 05946-252300 Email: universalenterprises111@gmail.com

Camera1/2.7" CMOS Sensor, 2.07M Effective PixelsAngle of View (Horizontal & Vertical) $72^{\circ} - 6.9^{\circ} \& 44.8^{\circ} - 3.9^{\circ}$ Minimal Illumination $0.5 \text{ Lux } @ (F1.8, AGC ON)$ Optical Zoom $12x$ Digital Zoom $16x$ Lens $F3.5 \text{mm-}42.3 \text{mm, } F1.8 - F2.8 \text{ with Auto and Manual Focus}$ Camera Resolution $1080p 60 \text{fps, } 1080p 30 \text{fps}$ Shutter $1/30s \sim 1/10000s$ White BalanceAuto, Indoor, Outdoor, One Push, Manual	
Minimal Illumination         0.5 Lux @ (F1.8, AGC ON)           Optical Zoom         12x           Digital Zoom         16x           Lens         F3.5mm-42.3mm, F1.8 - F2.8 with Auto and Manual Focus           Camera Resolution         1080p 60fps, 1080p 30fps           Shutter         1/30s ~ 1/10000s	
Optical Zoom         12x           Digital Zoom         16x           Lens         F3.5mm-42.3mm, F1.8 - F2.8 with Auto and Manual Focus           Camera Resolution         1080p 60fps, 1080p 30fps           Shutter         1/30s ~ 1/10000s	
Digital Zoom         16x           Lens         F3.5mm-42.3mm, F1.8 - F2.8 with Auto and Manual Focus           Camera Resolution         1080p 60fps, 1080p 30fps           Shutter         1/30s ~ 1/10000s	
Lens       F3.5mm-42.3mm, F1.8 - F2.8 with Auto and Manual Focus         Camera Resolution       1080p 60fps, 1080p 30fps         Shutter       1/30s ~ 1/10000s	
Camera Resolution         1080p 60fps, 1080p 30fps           Shutter         1/30s ~ 1/10000s	
Shutter 1/30s ~ 1/10000s	
7.11	
White Balance Auto, Indoor, Outdoor, One Push, Manual	
Digital Noise Reduction 2D&3D Digital Noise Reduction	
Speed Range (Pan & Tilt) 1.7° – 100°/S & 1.7° – 69.9°/S	
Pan and Tilt ±170 degree & -30 degree - +90 degree	
Camera Features Supported Backlight Compensation, Image Freeze, H & V Flip	
Number of Presets and accuracy and Storage 255, 0.1°, Minimum 100 Presets	
Video Resolutions         1080p, 720p, 540p, 480p, 360p, 240p	
Audio Encoding AAC audio encoding for better sound quality and smaller bandwidth	
Low Light High SNR of CMOS sensor even under low illumination conditions picture can	keep
clean and clear	
Sound to Noise Ratio (SNR) >55dB	
Remote Control  All parameters of the camera remotely controlled by the high-speed	
communications, handheld remote control	
Interface (Video) USB 3.0 x 1, USB 2.0 x 1, RS232 IN, RJ45 x 1 (10M/100M adaptive ethernet po	rt),
Audio In 3.5mm x 1, HDMI x 1	
Operate System Supported Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android	
Video Format 1080P@60fps, 1080P@30fps, (YUY2 / H.264 / MJPEG)	
Audio on USB Support	
USB Video Communication Protocol UVC 1.5	
Video Compression H.264/MJEPG, H.265	
Video Stream         Main Stream Resolution(1920x1080,1280x720,1024x576), Sub Stream Resolution(1920x1080,1280x720,1024x576), Sub Stream Resolution(1920x1080,1280x720,1024x576)	tion
Video Bit Rate 328Kbps ~ 20480Kbps (Variable Rate & Fixed Rate)	
Frame Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps	
Audio Bit Rate AAC 96Kbps, 128Kbps, 256Kbps	
Support protocols TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast	
Accessories IR remote control, USB cable, Power adaptor and cable, user manual	
Mounting Type Ceiling and Wall Mount	
Power Consumption 12W (Max)	
Current Consumption 12V - 1.0A(MAX) / 5V - 1.5A(MAX)	
Temperature Operating: -10°C ~ 40°C; Storage: -40°C ~ 60°C	
Input Voltage DC 12V, USB DC	

Product image(s) are for illustrative purposes only and may differ from the actual product



## UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand) Ph.: 05946-255434, Fax: 05946-252300 Email: universalenterprises111@gmail.com