



Video Conferencing Camera



Record your meeting in full HD



Best device for virtual conference



Easy to setup and mounting option



Comes with optical and digital zoom

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com

Video Conferencing Camera – UE-CAM-10A	
Sensor	1/2.8", CMOS, Effective Pixel: 2.07M
Scanning Mode	Progressive
Lens	f3.5mm ~ 42.3mm, F1.8 ~ F2.8
Optical / Digital Zoom	10x /12x
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Backlight Compensation	Support
Digital Noise Reduction	Solution supplied with minimum 4 Wireless expansion microphones
Video S/N	≥55dB
Field of View	80°
Horizontal Rotation Range	±170°
Vertical Rotation Range	-30° ~ + 90°
Pan Speed Range	2.7° ~ 35°/sec
Tilt Speed Range	1.7° ~ 31° /sec
H & V Flip	Support
Image Freeze	Support
Number of Pre-set	255, 10 pre-sets on Remote control
Pre-set Accuracy	0.1°
Video System	1080p/60, 1080p/50, 1080p/30, 1080p/25
Operate System	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Colour System	YUY2 / H.264 / MJPEG
Video Format	YUY2 (ISOC): 1080P@60fps, H.264 AVC/SVC: 1080P@60fps, MJPEG: 1080P@60fps
Audio on USB	Support
USB Video Communication Protocol	UVC 1.1~1.5
Video	H.264/MJPEG
Video Stream	Main Stream, Sub Stream
Main Stream Resolution	1920x1080, 1280x720, 1024x576
Sub Stream Resolution	1280x720, 720x576, 320x240
Video Bit Rate	328Kbps ~ 20480Kbps
Bit Rate Type	Variable Rate, Fixed Rate

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
 Ph.: 05946-255434, Fax: 05946-252300
 Email: universalenterprises111@gmail.com

Frame Rate	50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps
Audio	AAC
Audio Bit Rate	96Kbps, 128Kbps, 256Kbps
Support protocols	TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast
Redundant Power Supply	Device Support Minimum three power supply method for power redundancy Supports USB 5V power supply, 12V power adapter power supply and PoE power supply.
PoE Power Supply & Controlling	Device Support PoE power supply for control, Video and audio only need one network cable.
Simultaneous Video Output	Device support HDMI, USB3.0 and LAN interface-based Video output HD video at the same time
Low Light	Device support High SNR of CMOS sensor, even under low illumination conditions, picture can still keep clean and clear.
Remote Control	All the parameters of the camera can be remote controlled by the high-speed communications
Video Output	1xUSB3.0, 1x HDMI, 1x RJ45
Network Interface	1xRJ45: 10M/100M Ethernet Interface
USB Interface	1x USB 3.0 Type-C
Audio Interface	1-ch: 3.5mm Audio Interface Line In
Communication Interface	1xRS232 In, 1xRS485
Power Jack	JEITA type (DC IN 12V)
Input Voltage	DC 12V, DC 5V, PoE(802.3af)
Current Consumption	12V - 1.0A(MAX) / 5V - 1.5A(MAX)
Operating Temperature	-10°C ~ 40°C
Storage Temperature	-40°C ~ 60°C
Power Consumption	12W

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
 Ph.: 05946-255434, Fax: 05946-252300
 Email: universalenterprises111@gmail.com